

SC73462*Fastener Type:*

C-ring, 16 Ga., 3/8", 130 per stick

Applications:

Traps and pots, arts and crafts projects, cords, cables and light wire to wire applications, netting/mesh

Tool Description:

Operating Range of SC73462 Tool: 1/16" – 1/8"

Ring Capacity: 150 Rings

Size: 3.7"x7.4"x10.6"

Weight: 2.9 lbs.

Air Consumption: 3.3 [CFM@100Cyc/Min](#)**SC760, SC761***Fastener Type:*

C-ring, 16 Ga., 1/2", 100 per stick

Applications:

Traps and pots, arts and crafts projects, shock cords, small ropes, cables and medium gauge wire to wire applications, netting/mesh, electrical cord strain relief

Tool Description:

Operating Range of SC760 Tool: 1/8" – 7/32"

Operating Range of SC761 Tool: 3/16" – 7/32"

Ring Capacity: 145 Rings

Size: 3.8"x7.4"x10.6"

Weight: 3.0 lbs.

Air Consumption: 3.3 [CFM@100Cyc/Min](#)**SC460CT***Fastener Type:*

C-ring, 16 Ga., 1/2", 100 per stick

Applications:

Bagging, packaging, oil absorption socks, arts and crafts projects, cords, small ropes, electrical cord strain relief

Tool Description:

Operating Range of SC760CT Tool: 1/8" – 7/32"

Mounted Tool, Gravity feed magazine

Ring Capacity: 325 Rings

Size: 8.0"x15.0"x23.0"

Weight: 7.4 lbs.

Air Consumption: 3.3 [CFM@100Cyc/Min](#)**SC742***Fastener Type:*

C-ring, 16 Ga., 3/4", 110 per stick

Applications:

Traps and cages, nursery tagging/ball & burlap, novelty items (key chains etc.), arts and crafts projects, medium ropes, cables and medium gauge wire to heavy gauge wire application, electrical cord strain relief, packaging / bag closure, cable assemblies, silt fencing / erosion control, securing fence wire / mesh, automotive seating, furniture / upholstery, bedding, misc. production / assembly applications

Tool Description:

Operating Range of SC742 Tool: 3/16" – 11/32"

Short Magazine

Ring Capacity: 125 Rings

Size: 3.9"x7.4"x10.8"

Weight: 3.3 lbs.

Air Consumption: 3.3 [CFM@100Cyc/Min](#)**SC743, SC743SG***Fastener Type:*

C-ring, 16 Ga., 3/4", 110 per stick

Applications:

Traps and cages, nursery tagging/ball & burlap, novelty items (key chains etc.), arts and crafts projects, medium ropes, cables and medium gauge wire to heavy gauge wire application, electrical cord strain relief, packaging / bag closure, cable assemblies, silt fencing / erosion control, securing fence wire / mesh, automotive seating, furniture / upholstery, bedding, misc. production / assembly applications

Tool Description:

Operating Range of SC743 Tool: 3/16" – 11/32"

Operating Range of SC743SG Tool: 13/32" – 7/16"

Ring Capacity: 155 Rings

Size: 3.5"x7.4"x13.2"

Weight: 2.8 lbs.

Air Consumption: [3.3CFM@100](#) Cyc/Min**SC7, SC7C, SC7E***Fastener Type:*

C-ring, 15 Ga., 3/4", 100 per stick

Applications:

Automotive seating, furniture / upholstery, bedding, traps and cages, arts and crafts projects, medium ropes, cables and medium gauge wire to heavy gauge wire application, electrical cord strain relief, shock cords (bungee), packaging / bag closure, cable assemblies, silt fencing / erosion control, misc. production / assembly applications

Tool Description:

Operating Range of SC7 Tool: 5/16" – 27/64"

Operating Range of SC7C Tool: 3/16" – 11/32"

Operating Range of SC7E Tool: 5/16" – 27/64"

Ring Capacity: 125 Rings

Size: 3.5"x7.4"x13.2"

Weight: 2.8 lbs.

SC7E Ring Closure: 5/16" minimum

Ring Capacity: 125 Rings

Size: 3.5"x7.4"x13.9"

Weight: 2.9 lbs.

Air Consumption: 3.3 [CFM@100](#) Cyc/Min**SC77XE***Fastener Type:*

C-ring, 15 Ga., 3/4", 100 per stick

Applications:

Automotive seating, furniture / upholstery, misc. production / assembly applications

Tool Description:

Operating Range of SC77XE Tool: 5/16" – 27/64"

Ring Capacity: 125 Rings

Size: 3.5"x7.5"x15.0"

Weight: 3.3 lbs.

Air Consumption: 3.3 [CFM@100](#) Cyc/Min**SC4LWH***Fastener Type:*

C-ring, 15 Ga., 3/4", 100 per stick

Applications:

Automotive seating, furniture / upholstery, bedding, misc. production / assembly applications

Tool Description:

Operating Range of SC4LWH Tool: 5/16" – 27/64"

Ring Capacity: 140 Rings

Size: 3.2"x7.8"x13.4"

Weight: 3.7 lbs.

Air Consumption: 3.3 [CFM@100](#) Cyc/Min

TLMT1714C*Fastener Type:*

C-ring, 14 Ga., 1-1/16", 100 per stick

Applications:

Bagging, packaging, cable assembly, oil absorption socks, arts and crafts projects, shock cords (bungee), ropes, misc. production / assembly applications

Tool Description:

Operating Range of TLMT1714C Tool: 13/23" – 15/32"

Mounted Tool with Foot Trip Switch

Ring Capacity: 125 Rings

Size: 4.1"x14.2"x13.0"

Weight: 9.2 lbs.

Air Consumption: 6.3 [CFM@50](#) Cyc/Min**SC50T***Fastener Type:*

C-ring, 11 Ga., 1-1/2", 40 per stick

Applications:

Ropes/swingsets, bagging, packaging, oil absorption socks, arts and crafts projects, shock cords, concrete reinforcement wire (not rebar), cables and large gauge wire to wire applications, securing fence wire/mesh, electrical cord strain relief, misc. production / assembly applications

Tool Description:

Operating Range of SC50T Tool: .410" – .513"

Ring Capacity: 125 Rings

Size: 9.0"x12.1"x20.0"

Weight: 14.3 lbs.

Air Consumption: 10.4 [CFM@50](#) Cyc/Min**TR201, TR203 Spring Return Tool***Fastener Type:*

D-ring, 15 Ga., 3/4", 50 per stick

Applications:

Bedding, fencing, securing fencing wire/mesh, arts and crafts projects, packaging / bag closure, automotive seating, furniture / upholstery, misc. production / assembly applications

Tool Description:

Operating Range of "TR201" Tool: 1/4" – 3/8"

TR201 Spring Return Tool

Ring Capacity: 55 Rings

Size: 3.5"x10.3"x7.8"

Weight: 3.3 lbs.

Operating Range of "TR203" Tool: 1/4" – 3/8"

TR203 Spring Return Tool

Ring Capacity: 125 Rings

Size: 3.5"x10.3"x15.8"

Weight: 3.6 lbs.

Air Consumption: 1.6 [CFM@100](#) Cyc/Min**TR315 Air Return Tool***Fastener Type:*

D-ring, 15 Ga., 3/4", 100 per stick

Applications:

Bedding, fencing, securing fencing wire/mesh, arts and crafts projects, packaging / bag closure, automotive seating, furniture / upholstery, misc. production / assembly applications

Tool Description:

Operating Range of "TR315" Tool: 1/4" – 3/8"

Ring Capacity: 125 Rings

Size: 3.3"x9.9"x15.8"

Weight: 3.6 lbs.

Air Consumption: 3.3 [CFM@100](#) Cyc/Min**Ringer9/16 (Hand Pliers)***Fastener Type:*

D-ring, 15 Ga., 9/16", 50 per stick

Applications:

Traps/cages, arts and crafts projects, bag closure, upholstery, nursery, fencing wire/mesh, production / assembly applications

Tool Description:

Operating Range of RINGER9/16 Tool: 3/16"

Ring Capacity: 75 Rings

Size: 2.0"x7.0"x7.0"

Weight: 0.8 lbs.

P7 (Hand Pliers)*Fastener Type:*

C-ring, 16 Ga., 11/16", 50 per stick

Applications:

Traps/cages, arts and crafts projects, bag closure, upholstery, nursery, fencing wire/mesh, production / assembly applications

Tool Description:

Operating Range of P7 Tool: 9/32"

Ring Capacity: 55 Rings

Size: 1.1"x3.7"x7.2"

Weight: 0.7 lbs.

HFP9 (Hand Pliers)*Fastener Type:*

D-ring, 9 Ga., 1-3/16", 25 per stick

Applications:

Wire fence installation, arts and crafts projects, bag closure, production / assembly applications

Tool Description:

Operating Range of HFP9 Tool: 7/16"

Ring Capacity: 27 Rings

Size: 4.2"x8.0"x8.0"

Weight: 1.3 lbs.

SC50HP (Hand Pliers)*Fastener Type:*

C-ring, 11 Ga., 1-1/2", 40 per stick

Applications:

Ropes, bagging, packaging, arts and crafts projects, concrete reinforcement wire (not rebar), cables and large gauge wire to wire applications, securing fence wire/mesh, misc. production / assembly applications

Tool Description:

Operating Range of SC50HP Tool: .410" – .513"

Ring Capacity: 42 Rings

Size: 5.0"x6.3"x27.0"

Weight: 9.7 lbs.